



## OBJT2.E365580 Single- and Multi-layer Insulated Winding Wire - Component

[Page Bottom](#)

### Single- and Multi-layer Insulated Winding Wire - Component

[See General Information for Single- and Multi-layer Insulated Winding Wire - Component](#)**DONGGUAN KOSHEN INSULATOR CO LTD**

E365580

B702 7F Longzhixiang Technology Park


2 HuaguoShan Rd

Xin An Community Changan Town

Dongguan, Guangdong CHINA

Cat. No.	Insulation Type	TIW Conductor Size Range	Temp Class °C	Rated Volts UL 60950-1 V peak	Rated Volts UL 60601-1 V rms
<b>TIW-1- (Suffix)</b>	Reinforced	32 - 18 AWG	130(B)	1410	-
<b>TIW-1-LZ</b>	Reinforced	0.1mm x 7 trips - 0.3mm x 7 strips(cross sectional area 0.019 mm <sup>2</sup> to 0.8mm <sup>2</sup> )	130(B)	1410	-
<b>TIW-B- (Suffix)</b>	Reinforced	0.156 - 1.002 mm	130(B)	1410	-
<b>TIW-B-LZ</b>	Reinforced	0.1mm x 7 trips - 0.3mm x 7 strips(cross sectional area 0.019 mm <sup>2</sup> to 0.8mm <sup>2</sup> )	130(B)	1410	-

(Suffix) - are replaced by (Blank), (B) and (M) to indicate the following conductor types: (Blank): Solid bare copper; (B): R/C - Magnet Wires (OBMW2), ANSI MW type: MW 5, MW 24, MW 76, MW 30, MW 74, MW 35, MW 36, MW 38 and MW73.; (M): R/C - Magnet Wires (OBMW2), ANSI MW type: MW 28, MW 75, MW 79, MW 80, MW 82, MW83.

Marking: Company name, material designation and the Recognized Component Mark,  on the smallest unit container in which the product is packaged, spool, or on a tag attached to the end of the wire.

[Last Updated](#) on 2017-03-27[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".